



PRODUCT

NALCO 23230 LIQUID

Emergency Telephone Number

Medical (800) 462-5378 (24 hours)

(800) I-M-ALERT

SECTION 4 FIRST AID INFORMATION

(CONTINUED)

depression and convulsions may be needed.

SECTION 5 HEALTH EFFECTS INFORMATION

PRIMARY ROUTE(S) OF EXPOSURE: Eye, Skin

EYE CONTACT: Can cause severe irritation and acidic type burns.
SKIN CONTACT: Can cause severe irritation and acidic type burns.

SYMPTOMS OF EXPOSURE: A review of available data does not identify any symptoms from exposure not previously mentioned.

AGGRAVATION OF EXISTING CONDITIONS: A review of available data does not identify any worsening of existing conditions.

SECTION 6 TOXICOLOGY INFORMATION

TOXICITY STUDIES: No toxicity studies have been conducted on this product.

SECTION 7 PHYSICAL AND CHEMICAL PROPERTIES

COLOR:	Clear to hazy, light yellow to amber	FORM:	Liquid
DENSITY:	10.0-10.8 lbs/gal.		
SPECIFIC GRAVITY:	1.20-1/30 @ 77 Degrees F		ASTM D-1298
pH (NEAT) =	0-2		ASTM E-70
FREEZE POINT:	Less than -50 Degrees F		ASTM D-1177
VISCOSITY:	12 cps @ 72 Degrees F		ASTM D-2983
FLASH POINT:	None (PMCC)		ASTM D-93

NOTE: These physical properties are typical values for this product.

SECTION 8 FIRE AND EXPLOSION INFORMATION

FLASH POINT: None (PMCC) ASTM D-93

EXTINGUISHING MEDIA: Not applicable

UNUSUAL FIRE AND EXPLOSION HAZARD: Treat like an acid fire.

SECTION 9 REACTIVITY INFORMATION

INCOMPATIBILITY: Avoid alkaline materials (eg. ammonia and its solutions, carbonates, sodium hydroxide (caustic), potassium hydroxide, calcium hydroxide (lime), cyanides, sulfides, hypochlorites, chlorites) which can generate heat



MATERIAL SAFETY DATA SHEET

PRODUCT

NALCO 23230 LIQUID

Emergency Telephone Number

Medical (800) 462-5378 (24 hours)

(800) I-M-ALERT

SECTION 9 REACTIVITY INFORMATION

(CONTINUED)

with splattering or boiling and the release of toxic fumes.

THERMAL DECOMPOSITION PRODUCTS: In the event of combustion CO, CO₂, NO_x, SO_x, HCl may be formed. Do not breathe smoke or fumes. Wear suitable protective equipment.

SECTION 10 PERSONAL PROTECTION EQUIPMENT

RESPIRATORY PROTECTION: Respiratory protection is not normally needed since the volatility and toxicity are low. If significant vapors, mists or aerosols are generated, wear a NIOSH approved or equivalent respirator.

For large spills, entry into large tanks, vessels or enclosed small spaces with inadequate ventilation, a pressure-demand, self-contained breathing apparatus is recommended.

VENTILATION: General ventilation is recommended.

PROTECTIVE EQUIPMENT: Wear impermeable gloves, boots, apron and a face shield with chemical splash goggles. Examples of impermeable gloves available on the market are neoprene, nitrile, PVC, natural rubber, viton and butyl (compatibility studies have not been performed). A full slicker suit is recommended if gross exposure is possible.

The availability of an eye wash fountain and safety shower is recommended.

If clothing is contaminated, remove clothing and thoroughly wash the affected area. Launder contaminated clothing before reuse.

SECTION 11 SPILL AND DISPOSAL INFORMATION

IN CASE OF TRANSPORTATION ACCIDENTS, CALL THE FOLLOWING 24-HOUR TELEPHONE NUMBER (708-920-1510)

SPILL CONTROL AND RECOVERY:

Small liquid spills: Contain with absorbent material, such as clay, soil or any commercially available absorbent. Shovel reclaimed liquid and absorbent into recovery or salvage drums for disposal. Refer to CERCLA in Section 14.

Large liquid spills: Dike to prevent further movement and reclaim into recovery or salvage drums or tank truck for disposal. Refer to CERCLA in Section 14.



MATERIAL SAFETY DATA SHEET

PRODUCT

NALCO 23230 LIQUID

Emergency Telephone Number

Medical (800) 462-5378 (24 hours)

(800) I-M-ALERT

SECTION 11 SPILL AND DISPOSAL INFORMATION

(CONTINUED)

For large indoor spills, evacuate employees and ventilate area. Those responsible for control and recovery should wear the protective equipment specified in Section 10.

DISPOSAL: If this product becomes a waste, it meets the criteria of a hazardous waste as defined under the Resources Conservation and Recovery Act (RCRA) 40 CFR 261. Hazardous Waste D002.

As a hazardous liquid waste, it must be solidified with stabilizing agents (such as sand, fly ash, or cement) so that no free liquid remains before disposal to a licensed industrial waste landfill (Hazardous Waste Treatment, Storage and Disposal facility). A hazardous liquid waste can also be deep-well injected in accordance with local, state, and federal regulations.

SECTION 12 ENVIRONMENTAL INFORMATION

If released into the environment, see CERCLA in Section 14.

SECTION 13 TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME/HAZARD CODE - CORROSIVE LIQUID, N.O.S.,
8, UN 1760, PG III
CONTAINS - PHOSPHORIC ACID,
ZINC CHLORIDE

SECTION 14 REGULATORY INFORMATION

The following regulations apply to this product.

FEDERAL REGULATIONS:

OSHA'S HAZARD COMMUNICATION RULE, 29 CFR 1910.1200:

Based on our hazard evaluation, the following ingredients in this product are hazardous and the reasons are shown below.

Zinc chloride - Severe irritant

Zinc chloride fume = TWA 1 mg/m³, STEL 2 mg/m³ ACGIH/TLV
Phosphoric acid = TWA 1 mg/m³, STEL 3 mg/m³ ACGIH/TLV

Zinc chloride fume = TWA 1 mg/m³, STEL 2 mg/m³ OSHA/PEL
Phosphoric acid = TWA 1 mg/m³, STEL 3 mg/m³ OSHA/PEL

CERCLA/SUPERFUND, 40 CFR 117, 302:

MATERIAL SAFETY DATA SHEET



PRODUCT

NALCO 23230 LIQUID

Emergency Telephone Number

Medical (800) 462-5378 (24 hours)

(800) I-M-ALERT

SECTION 14 REGULATORY INFORMATION

(CONTINUED)

This product contains zinc chloride, a Reportable Quantity (RQ) substance and if 9,900 pounds of product are released, it requires notification to the NATIONAL RESPONSE CENTER, WASHINGTON, D. C. (1-800-424-8802).

SARA/SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986
(TITLE III) - SECTIONS 302, 311, 312 AND 313:

SECTION 302 - EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355):
This product does not contain ingredients listed in Appendix A and B as an Extremely Hazardous Substance.

SECTIONS 311 and 312 - MATERIAL SAFETY DATA SHEET REQUIREMENTS (40 CFR 370):
Our hazard evaluation has found this product to be hazardous. The product should be reported under the following EPA hazard categories:

- XX Immediate (acute) health hazard
- Delayed (chronic) health hazard
- Fire hazard
- Sudden release of pressure hazard
- Reactive hazard

SECTION 313 - LIST OF TOXIC CHEMICALS (40 CFR 372):
This product contains the following ingredient(s), (with CAS # and % range) which appear(s) on the List of Toxic Chemicals.

Zinc chloride	7646-85-7	10-20
Phosphoric acid	7664-38-2	5-10

TOXIC SUBSTANCES CONTROL ACT (TSCA):

The chemical ingredients in this product are on the 8(b) Inventory List (40 CFR 710).

RESOURCE CONSERVATION AND RECOVERY ACT (RCRA), 40 CFR 261 SUBPART C & D:
Consult Section 11 for RCRA classification.

FEDERAL WATER POLLUTION CONTROL ACT, CLEAN WATER ACT, 40 CFR 401.15
(formerly Sec. 307), 40 CFR 116 (formerly Sec. 311):

This product contains the following ingredients covered by the Clean Water Act:

Zinc chloride - Section 307, 311
Phosphoric acid - Section 311

CLEAN AIR ACT, Sec. 111 (40 CFR 60), Sec. 112 (40 CFR 61, 1990 Amendments),
Sec. 611 (40 CFR 82, CLASS I and II Ozone depleting substances):

**MATERIAL SAFETY DATA SHEET****PRODUCT**

NALCO 23230 LIQUID

Emergency Telephone Number

Medical (800) 482-5378 (24 hours)

(800) I-M-ALERT

SECTION 14 REGULATORY INFORMATION

(CONTINUED)

This product does not contain ingredients covered by the Clean Air Act.

STATE REGULATIONS:**CALIFORNIA PROPOSITION 65:**

This product does not contain any chemicals which require warning under California Proposition 65.

MICHIGAN CRITICAL MATERIALS:

This product contains the following substance identified on the Michigan Critical Materials Register:

Zinc chloride

STATE RIGHT TO KNOW LAWS:

Regulated in those states using the TLV for zinc chloride and phosphoric acid as a criteria for listing.

INTERNATIONAL REGULATIONS:

This is a WHMIS controlled product under The House of Commons of Canada Bill C-70 (Class E and D2B). The product contains the following substance(s), from the Ingredient Disclosure List or has been evaluated based on its toxicological properties, to contain the following hazardous ingredient(s):

Chemical Name	CAS #	% Concentration Range
Zinc chloride	7646-85-7	10-20
Phosphoric acid	7664-38-2	5-10

SECTION 15 ADDITIONAL INFORMATION

Nalco internal number F102110

SECTION 16 USER'S RESPONSIBILITY

This product material safety data sheet provides health and safety information. The product is to be used in applications consistent with our product literature. Individuals handling this product should be informed of the recommended safety precautions and should have access to this information. For any other uses, exposures should be evaluated so that appropriate handling practices and training programs can be established to ensure safe workplace operations. Please consult your local sales representative for any further information.



MATERIAL SAFETY DATA SHEET

PRODUCT

NALCO 23230 LIQUID

Emergency Telephone Number

Medical (800) 462-5378 (24 hours)

(800) I-M-ALERT

SECTION 17 BIBLIOGRAPHY

ANNUAL REPORT ON CARCINOGENS, U.S. Department of Health and Human Services, Public Health Service, PB 33-135855, 1983.

CASARETT AND DOULL'S TOXICOLOGY, THE BASIC SCIENCE OF POISONS, Doull, J., Klaassen, C. D., and Admur, M. O., eds., Macmillian Publishing Company, Inc., N. Y., 2nd edition, 1980.

CHEMICAL HAZARDS OF THE WORKPLACE, Proctor, N. H., and Hughes, J. P., eds., J. P. Lipincott Company, N.Y., 1981.

DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS, Sax, N. Irving, ed., Van Nostrand Reinhold Company, N.Y., 6th edition, 1984.

IARC MONOGRAPHS ON THE EVALUATION OF THE CARCINOGENIC RISK OF CHEMICALS TO MAN, Geneva: World Health Organization, International Agency for Research on Cancer, 1972-1977.

PATTY'S INDUSTRIAL HYGIENE AND TOXICOLOGY, Clayton, G. D., Clayton, F. E., eds., John Wiley and Sons, N. Y., 3rd edition, Vol. 2 A-C, 1981.

REGISTRY OF TOXIC EFFECTS ON CHEMICAL SUBSTANCES, U.S. Department of Health and Human Services, Public Health Service, Center for Disease Control, National Institute for Occupational Safety and Health, 1983 supplement of 1981-1982 edition, Vol. 1-3, OH, 1984.

Title 29 Code of Federal Regulations Part 1910, Subpart Z, Toxic and Hazardous Substances, Occupational Safety and Health Administration (OSHA).

THRESHOLD LIMIT VALUES FOR CHEMICAL SUBSTANCES AND PHYSICAL AGENTS IN THE WORKROOM ENVIRONMENT WITH INTENDED CHANGES, American Conference of Governmental Industrial Hygienists, OH.

PREPARED BY: Ricky A. Stackhouse PhD., Toxicologist
DATE CHANGED: 11/02/93
DATE PRINTED: 02/25/94



MATERIAL SAFETY DATA SHEET

PRODUCT

Emergency Telephone Number

Medical (800) 462-5378 (24 hours)

(800) I-M-ALERT



MATERIAL SAFETY DATA SHEET

PRODUCT

NALCO 8304T LIQUID

Emergency Telephone Number

Medical (800) 462-5378 (24 hours)

(800) I-M-ALERT

SECTION 1 PRODUCT IDENTIFICATION

TRADE NAME: NALCO 8304T LIQUID

DESCRIPTION: An aqueous blend of a sulfonated polyacrylate and a phosphonobutane carboxylate

NFPA 704M/HMIS RATING: 1/1 HEALTH 1/1 FLAMMABILITY 0/0 REACTIVITY 0 OTHER
0=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme

SECTION 2 HAZARDOUS INGREDIENTS

Our hazard evaluation of the ingredient(s) under OSHA's Hazard Communication Rule, 29 CFR 1910.1200 has found none of the ingredient(s) hazardous.

SECTION 3 PRECAUTIONARY LABEL INFORMATION

CAUTION: May cause irritation to skin and eyes. Avoid contact with skin, eyes and clothing. Do not take internally.

Empty containers may contain residual product. Do not reuse container unless properly reconditioned.

SECTION 4 FIRST AID INFORMATION

EYES: Flush with water for 15 minutes. Call a physician.
SKIN: Flush with water for 15 minutes.
INGESTION: Do not induce vomiting. Give water. Call a physician.
INHALATION: Remove to fresh air. Treat symptoms. Call a physician.

NOTE TO PHYSICIAN: Based on the individual reactions of the patient, the physician's judgment should be used to control symptoms and clinical condition.

CAUTION: If unconscious, having trouble breathing or in convulsions, do not induce vomiting or give water.

SECTION 5 HEALTH EFFECTS INFORMATION

PRIMARY ROUTE(S) OF EXPOSURE: Eye, Skin

EYE CONTACT: May cause irritation with prolonged contact.
SKIN CONTACT: May cause irritation with prolonged contact.

SYMPTOMS OF EXPOSURE: A review of available data does not identify any symptoms from exposure not previously mentioned.

AGGRAVATION OF EXISTING CONDITIONS: A review of available data does not



PRODUCT

NALCO 8304T LIQUID

Emergency Telephone Number

Medical (800) 462-5378 (24 hours)

(800) I-M-ALERT

SECTION 5 HEALTH EFFECTS INFORMATION

(CONTINUED)

identify any worsening of existing conditions.

SECTION 6 TOXICOLOGY INFORMATION

TOXICITY STUDIES: No toxicity studies have been conducted on this product.

SECTION 7 PHYSICAL AND CHEMICAL PROPERTIES

COLOR: Yellow	FORM: Liquid	
DENSITY:	9.2 lbs/gal.	
SPECIFIC GRAVITY:	1.1 @ 77 Degrees F	ASTM D-1298
PH (NEAT) =	4 - 5	ASTM E-70
FREEZE POINT:	29 Degrees F	ASTM D-1177
FLASH POINT:	None (PMCC)	ASTM D-93

NOTE: These physical properties are typical values for this product.

SECTION 8 FIRE AND EXPLOSION INFORMATION

FLASH POINT: None (PMCC) ASTM D-93

EXTINGUISHING MEDIA: This product would not be expected to burn unless all the water is boiled away. The remaining organics may be ignitable. Use water to cool containers exposed to fire.

UNUSUAL FIRE AND EXPLOSION HAZARD: May evolve NO_x or SO_x under fire conditions.

SECTION 9 REACTIVITY INFORMATION

INCOMPATIBILITY: None known

THERMAL DECOMPOSITION PRODUCTS: In the event of combustion CO, CO₂, NO_x, SO_x may be formed. Do not breathe smoke or fumes. Wear suitable protective equipment.

SECTION 10 PERSONAL PROTECTION EQUIPMENT

RESPIRATORY PROTECTION: Respiratory protection is not normally needed. If significant mists or aerosols are generated, wear a NIOSH approved or equivalent respirator.

For large spills, entry into large tanks, vessels or enclosed small spaces with inadequate ventilation, a pressure-demand, self-contained breathing apparatus is recommended.

MATERIAL SAFETY DATA SHEET



PRODUCT

NALCO 8304T LIQUID

Emergency Telephone Number

Medical (800) 462-5378 (24 hours)

(800) I-M-ALERT

SECTION 10 PERSONAL PROTECTION EQUIPMENT

(CONTINUED)

VENTILATION: General ventilation is recommended.

PROTECTIVE EQUIPMENT: Use impermeable gloves and chemical splash goggles when attaching feeding equipment, doing maintenance or handling product. Examples of impermeable gloves available on the market are neoprene, nitrile, PVC, natural rubber, viton and butyl (compatibility studies have not been performed).

The availability of an eye wash fountain and safety shower is recommended.

If clothing is contaminated, remove clothing and thoroughly wash the affected area. Launder contaminated clothing before reuse.

SECTION 11 SPILL AND DISPOSAL INFORMATION

IN CASE OF TRANSPORTATION ACCIDENTS, CALL THE FOLLOWING 24-HOUR TELEPHONE NUMBER (800) I-M-ALERT or (800) 462-5378.

SPILL CONTROL AND RECOVERY:

Small liquid spills: Contain with absorbent material, such as clay, soil or any commercially available absorbent. Shovel reclaimed liquid and absorbent into recovery or salvage drums for disposal. Refer to CERCLA in Section 14.

Large liquid spills: Dike to prevent further movement and reclaim into recovery or salvage drums or tank truck for disposal. Refer to CERCLA in Section 14.

DISPOSAL: If this product becomes a waste, it does not meet the criteria of a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261, since it does not have the characteristics of Subpart C, nor is it listed under Subpart D.

As a non-hazardous liquid waste, it should be solidified with stabilizing agents (such as sand, fly ash, or cement) so that no free liquid remains before disposal to an industrial waste landfill. A non-hazardous liquid waste can also be incinerated in accordance with local, state, and federal regulations.

SECTION 12 ENVIRONMENTAL INFORMATION

Results below are based on a similar product.

96 hour static acute LC50 to Bluegill Sunfish = Greater than 1,000 mg/L



PRODUCT

NALCO 8304T LIQUID

Emergency Telephone Number

Medical (800) 462-5378 (24 hours)

(800) I-M-ALERT

SECTION 12 ENVIRONMENTAL INFORMATION

(CONTINUED)

96 hour no observed effect concentration is 1,000 mg/L based on no mortality or abnormal effects.

TOXICITY RATING: Essentially non-toxic

96 hour static acute LC50 to Rainbow Trout = 710 mg/L

96 hour no observed effect concentration is 125 mg/L based on no mortality or abnormal effects.

TOXICITY RATING: Slightly toxic

48 hour static acute EC50 to Daphnia magna = Greater than 1,000 mg/L

48 hour no observed effect concentration is 1,000 mg/L based on no mortality or abnormal effects.

TOXICITY RATING: Essentially non-toxic

If released into the environment, see CERCLA in Section 14.

SECTION 13 TRANSPORTATION INFORMATION

PROPER SHIPPING NAME/HAZARD CODE -
(DEPENDENT UPON MODE, PACKAGE)

PRODUCT IS NOT REGULATED
DURING TRANSPORTATION

SECTION 14 REGULATORY INFORMATION

The following regulations apply to this product.

FEDERAL REGULATIONS:

OSHA HAZARD COMMUNICATION RULE, 29 CFR 1910.1200:
Based on our hazard evaluation, none of the ingredients in this product are hazardous.

CERCLA/SUPERFUND, 40 CFR 117, 302:
Notification of spills of this product is not required.

SARA/SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986
(TITLE III) - SECTIONS 302, 311, 312 AND 313:

SECTION 302 - EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355):



MATERIAL SAFETY DATA SHEET

PRODUCT

NALCO 8304T LIQUID

Emergency Telephone Number

Medical (800) 462-5378 (24 hours)

(800) I-M-ALERT

SECTION 14 REGULATORY INFORMATION

(CONTINUED)

This product does not contain ingredients listed in Appendix A and B as an Extremely Hazardous Substance.

SECTIONS 311 and 312 - MATERIAL SAFETY DATA SHEET REQUIREMENTS (40 CFR 370):
Our hazard evaluation has found that this product is not hazardous under 29 CFR 1910.1200.

SECTION 313 - LIST OF TOXIC CHEMICALS (40 CFR 372):
This product does not contain ingredients on the List of Toxic Chemicals.

TOXIC SUBSTANCES CONTROL ACT (TSCA):
The chemical ingredients in this product are on the 8(b) Inventory List (40 CFR 710).

RESOURCE CONSERVATION AND RECOVERY ACT (RCRA), 40 CFR 261 SUBPART C & D:
Refer to Section 11 for RCRA classification.

FEDERAL WATER POLLUTION CONTROL ACT, CLEAN WATER ACT, 40 CFR 401.15/
formerly Sec. 307, 40 CFR 116/formerly Sec. 311:
None of the ingredients are specifically listed.

CLEAN AIR ACT, Sec. 111 (40 CFR 60), Sec. 112 (40 CFR 61, 1990 Amendments),
Sec. 611 (40 CFR 82, CLASS I and II Ozone depleting substances):
This product does not contain ingredients covered by the Clean Air Act.

STATE REGULATIONS:

CALIFORNIA PROPOSITION 65:
This product does not contain any chemicals which require warning under California Proposition 65.

MICHIGAN CRITICAL MATERIALS:
This product does not contain ingredients listed on the Michigan Critical Materials Register.

STATE RIGHT TO KNOW LAWS:
The following ingredient(s) are disclosed for compliance with State Right To Know Laws:

Sulfonated polyacrylate

Trade:

OSHA HAZARD COMMUNICATION RULE, 29 CFR 1910.1200:
Based on our hazard evaluation, none of the ingredients in this product are hazardous.

PAGE 5 OF 8



MATERIAL SAFETY DATA SHEET

PRODUCT

NALCO 8304T LIQUID

Emergency Telephone Number

Medical (800) 462-5378 (24 hours)

(800) I-M-ALERT

SECTION 14 REGULATORY INFORMATION

(CONTINUED)

CERCLA/SUPERFUND, 40 CFR 117, 302:
Notification of spills of this product is not required.

SARA/SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986
(TITLE III) - SECTIONS 302, 311, 312 AND 313:

SECTION 302 - EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355):
This product does not contain ingredients listed in Appendix A and B as an Extremely Hazardous Substance.

SECTIONS 311 and 312 - MATERIAL SAFETY DATA SHEET REQUIREMENTS (40 CFR 370):
Our hazard evaluation has found that this product is not hazardous under 29 CFR 1910.1200.

SECTION 313 - LIST OF TOXIC CHEMICALS (40 CFR 372):
This product does not contain ingredients on the List of Toxic Chemicals.

TOXIC SUBSTANCES CONTROL ACT (TSCA):
The chemical ingredients in this product are on the 8(b) Inventory List (40 CFR 710).

RESOURCE CONSERVATION AND RECOVERY ACT (RCRA), 40 CFR 261 SUBPART C & D:
Refer to Section 11 for RCRA classification.

FEDERAL WATER POLLUTION CONTROL ACT, CLEAN WATER ACT, 40 CFR 401.15/
formerly Sec. 307, 40 CFR 116/formerly Sec. 311:
None of the ingredients are specifically listed.

CLEAN AIR ACT, Sec. 111 (40 CFR 60), Sec. 112 (40 CFR 61, 1990 Amendments),
Sec. 611 (40 CFR 82, CLASS I and II Ozone depleting substances):
This product does not contain ingredients covered by the Clean Air Act.

STATE REGULATIONS:

CALIFORNIA PROPOSITION 65:
This product does not contain any chemicals which require warning under California Proposition 65.

MICHIGAN CRITICAL MATERIALS:
This product does not contain ingredients listed on the Michigan Critical Materials Register.

STATE RIGHT TO KNOW LAWS:



MATERIAL SAFETY DATA SHEET

PRODUCT

NALCO 8304T LIQUID

Emergency Telephone Number

Medical (800) 462-5378 (24 hours)

(800) I-M-ALERT

SECTION 14 REGULATORY INFORMATION

(CONTINUED)

The following ingredient(s) are disclosed for compliance with State Right To Know Laws:

Sulfonated polyacrylate
Phosphonobutane carboxylate
Water

Trade secret
Trade secret
7732-18-5

INTERNATIONAL REGULATIONS:

This is not a WHMIS controlled product under The House of Commons of Canada Bill C-70.

SECTION 15 ADDITIONAL INFORMATION

Nalco internal number F100018

SECTION 16 USER'S RESPONSIBILITY

This product material safety data sheet provides health and safety information. The product is to be used in applications consistent with our product literature. Individuals handling this product should be informed of the recommended safety precautions and should have access to this information. For any other uses, exposures should be evaluated so that appropriate handling practices and training programs can be established to ensure safe workplace operations. Please consult your local sales representative for any further information.

SECTION 17 BIBLIOGRAPHY

ANNUAL REPORT ON CARCINOGENS, U.S. Department of Health and Human Services, Public Health Service, PB 33-135855, 1983.

CASARETT AND DOULL'S TOXICOLOGY, THE BASIC SCIENCE OF POISONS, Doull, J., Klaassen, C. D., and Admur, M. O., eds., Macmillan Publishing Company, Inc., N. Y., 2nd edition, 1980.

CHEMICAL HAZARDS OF THE WORKPLACE, Proctor, N. H., and Hughes, J. P., eds., J. P. Lipincott Company, N.Y., 1981.

DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS, Sax, N. Irving, ed., Van Nostrand Reinhold Company, N.Y., 6th edition, 1984.

IARC MONOGRAPHS ON THE EVALUATION OF THE CARCINOGENIC RISK OF CHEMICALS TO MAN, Geneva: World Health Organization, International Agency for



MATERIAL SAFETY DATA SHEET

PRODUCT

NALCO 8304T LIQUID

Emergency Telephone Number

Medical (800) 462-5378 (24 hours)

(800) I-M-ALERT

SECTION 17 BIBLIOGRAPHY

(CONTINUED)

Research on Cancer, 1972-1977.

PATTY'S INDUSTRIAL HYGIENE AND TOXICOLOGY, Clayton, G. D., Clayton, F. E., eds., John Wiley and Sons, N. Y., 3rd edition, Vol. 2 A-C, 1981.

REGISTRY OF TOXIC EFFECTS ON CHEMICAL SUBSTANCES, U.S. Department of Health and Human Services, Public Health Service, Center for Disease Control, National Institute for Occupational Safety and Health, 1983 supplement of 1981-1982 edition, Vol. 1-3, OH, 1984.

Title 29 Code of Federal Regulations Part 1910, Subpart Z, Toxic and Hazardous Substances, Occupational Safety and Health Administration (OSHA).

THRESHOLD LIMIT VALUES FOR CHEMICAL SUBSTANCES AND PHYSICAL AGENTS IN THE WORKROOM ENVIRONMENT WITH INTENDED CHANGES, American Conference of Governmental Industrial Hygienists, OH.

PREPARED BY: Ricky A. Stackhouse PhD., Toxicologist

DATE CHANGED: 12/30/93

DATE PRINTED: 06/06/94

**PRODUCT**

NALCO 71-D5 ANTIFOAM

Emergency Telephone Number

Medical (800) 462-5378 (24 hours)

(800) I-M-ALERT

SECTION 1 PRODUCT IDENTIFICATION

TRADE NAME: NALCO 71-D5 ANTIFOAM

DESCRIPTION: A blend of fatty acids, polyglycols, polyglycol ester, and oxyalkylate in kerosene and distillate

NFPA 704M/HMIS RATING: 1/1 HEALTH 1/1 FLAMMABILITY 0/0 REACTIVITY 0 OTHER
0=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme**SECTION 2 HAZARDOUS INGREDIENTS**

Our hazard evaluation has identified the following chemical ingredient(s) as hazardous under OSHA's Hazard Communication Rule, 29 CFR 1910.1200. Consult Section 14 for the nature of the hazard(s).

INGREDIENT(S)	CAS #	APPROX.%
Kerosene	8008-20-6	10-20
Straight run middle distillates	64741-44-2	40-70

SECTION 3 PRECAUTIONARY LABEL INFORMATION

CAUTION: May cause irritation to skin and eyes. Avoid contact with skin, eyes, and clothing. Avoid prolonged or repeated breathing of vapor. Use with adequate ventilation. Do not take internally.

Empty containers may contain residual product. Do not reuse container unless properly reconditioned.

SECTION 4 FIRST AID INFORMATION

EYES: Flush with water for 15 minutes. Call a physician.
SKIN: Wash thoroughly with soap and rinse with water. Call a physician.
INGESTION: Do not induce vomiting. Give water. Call a physician.
INHALATION: Remove to fresh air. Treat symptoms. Call a physician.

NOTE TO PHYSICIAN: Based on the individual reactions of the patient, the physician's judgment should be used to control symptoms and clinical condition.

CAUTION: If unconscious, having trouble breathing or in convulsions, do not induce vomiting or give water.

SECTION 5 HEALTH EFFECTS INFORMATION

PRIMARY ROUTE(S) OF EXPOSURE: Eye, Skin, Inhalation

PAGE 1 OF 9



MATERIAL SAFETY DATA SHEET

PRODUCT

NALCO 71-D5 ANTIFOAM

Emergency Telephone Number

Medical (800) 462-5378 (24 hours)

(800) I-M-ALERT

SECTION 5 HEALTH EFFECTS INFORMATION

(CONTINUED)

EYE CONTACT: Can cause mild, short-lasting irritation.
SKIN CONTACT: Can cause moderate irritation.
INHALATION: Prolonged inhalation of vapor may be harmful.

SYMPTOMS OF EXPOSURE:

ACUTE: Inhalation of high concentrations of product can cause nausea, dizziness, vomiting, stupor or unconsciousness.

CHRONIC: Prolonged skin contact with product can cause dry skin and defatting resulting in irritation and dermatitis.

AGGRAVATION OF EXISTING CONDITIONS: A review of available data does not identify any worsening of existing conditions.

SECTION 6 TOXICOLOGY INFORMATION

ACUTE TOXICITY STUDIES: Acute toxicity studies have been conducted on this product. The results are shown below.

ACUTE ORAL TOXICITY (ALBINO RATS): LD50 = Greater than 15,380 mg/kg

ACUTE DERMAL TOXICITY (ALBINO RABBITS): LD50 = Greater than 3,038 mg/kg

PRIMARY SKIN IRRITATION TEST (ALBINO RABBITS):

SKIN IRRITATION INDEX DRAIZE RATING: 3.1/8.0 Moderately irritating

PRIMARY EYE IRRITATION TEST (ALBINO RABBITS):

EYE IRRITATION INDEX DRAIZE RATING: 6.0/110.0 Minimal irritation

SECTION 7 PHYSICAL AND CHEMICAL PROPERTIES

COLOR: Pale straw	FORM: Liquid	ODOR: Faintly hydrocarbon
DENSITY:	6.9-7.5 lbs/gal.	
SOLUBILITY IN WATER:	Insoluble	
SPECIFIC GRAVITY:	0.83-0.90 @ 77 Degrees F	ASTM D-1298
VISCOSITY:	13.8 cps @ 80 Degrees F	ASTM D-2983
FREEZE POINT:	45 Degrees F	ASTM D-1177
POUR POINT:	45 Degrees F	ASTM D-97
FLASH POINT:	260 Degrees F (PMOC)	ASTM D-93
VAPOR PRESSURE:	0.6 mm Hg @ 68 Degrees F	
	1.3 mm Hg @ 100 Degrees F	
	4.4 mm Hg @ 150 Degrees F	ASTM D-323



MATERIAL SAFETY DATA SHEET

PRODUCT

NALCO 71-D5 ANTIFOAM

Emergency Telephone Number

Medical (800) 462-5378 (24 hours)

(800) I-M-ALERT

SECTION 7 PHYSICAL AND CHEMICAL PROPERTIES

(CONTINUED)

NOTE: These physical properties are typical values for this product.

SECTION 8 FIRE AND EXPLOSION INFORMATION

FLASH POINT: 260 Degrees F (PMCC) ASTM D-93

EXTINGUISHING MEDIA: Based on the NFPA guide, use dry chemical, foam, carbon dioxide or other extinguishing agent suitable for Class B fires. Use water to cool containers exposed to fire. For large fires, use water spray or fog, thoroughly drenching the burning material.

UNUSUAL FIRE AND EXPLOSION HAZARD: Containers exposed in a fire should be cooled with water to prevent vapor pressure buildup leading to a rupture.

SECTION 9 REACTIVITY INFORMATION

INCOMPATIBILITY: Avoid contact with strong oxidizers (eg. chlorine, peroxides, chromates, nitric acid, perchlorates, concentrated oxygen, permanganates) which can generate heat, fires, explosions and the release of toxic fumes.

STORAGE: Product should be stored at temperatures above 65 degrees F. If solidified, warm slowly (DO NOT USE LIVE STEAM) to 70-100 degrees F. Freezing does not reduce the efficiency of the product when properly reliquified.

THERMAL DECOMPOSITION PRODUCTS: In the event of combustion CO, CO2 may be formed. Do not breathe smoke or fumes. Wear suitable protective equipment.

SECTION 10 PERSONAL PROTECTION EQUIPMENT

RESPIRATORY PROTECTION: Respiratory protection is not normally needed since the volatility and toxicity are low. If significant vapors, mists or aerosols are generated, wear a NIOSH approved or equivalent respirator.

For large spills, entry into large tanks, vessels or enclosed small spaces with inadequate ventilation, a pressure-demand, self-contained breathing apparatus is recommended.

VENTILATION: General ventilation is recommended.

PROTECTIVE EQUIPMENT: Use impermeable gloves and chemical splash goggles when attaching feeding equipment or doing maintenance.

The availability of an eye wash fountain and safety shower is recommended.

**PRODUCT**

NALCO 71-D5 ANTIFOAM

Emergency Telephone Number

Medical (800) 462-5378 (24 hours)

(800) I-M-ALERT

SECTION 10 PERSONAL PROTECTION EQUIPMENT

(CONTINUED)

If clothing is contaminated, remove clothing and thoroughly wash the affected area. Launder contaminated clothing before reuse.

SECTION 11 SPILL AND DISPOSAL INFORMATION

IN CASE OF TRANSPORTATION ACCIDENTS, CALL THE FOLLOWING 24-HOUR TELEPHONE NUMBER (800) I-M-ALERT or (800) 462-5378.

SPILL CONTROL AND RECOVERY:

Small liquid spills: Contain with absorbent material, such as clay, soil or any commercially available absorbent. Shovel reclaimed liquid and absorbent into recovery or salvage drums for disposal. Refer to CERCLA in Section 14.

Large liquid spills: Dike to prevent further movement and reclaim into recovery or salvage drums or tank truck for disposal. Refer to CERCLA in Section 14.

DISPOSAL: If this product becomes a waste, trace levels of benzene may cause the product to be classified as a hazardous waste under the Resource Conservation and Recovery Act (RCRA) 40CFR261. Hazardous Waste D018. Before disposal, the product should be analyzed for its benzene content, to determine if it meets the criteria of a hazardous waste under RCRA (Toxicity Characteristic Leaching Procedure {TCLP} Test).

As a hazardous liquid waste, it must be solidified with stabilizing agents (such as sand, fly ash, or cement) so that no free liquid remains before disposal to a licensed industrial waste landfill (Hazardous Waste Treatment, Storage and Disposal facility). A hazardous liquid waste can also be incinerated in accordance with local, state, and federal regulations.

SECTION 12 ENVIRONMENTAL INFORMATION

BIOLOGICAL OXYGEN DEMAND (5-day BOD): 102,440 mg/L

CHEMICAL OXYGEN DEMAND (COD): 308,460 mg/L

TOTAL ORGANIC CARBON (TOC): 195,870 mg/L

AQUATIC DATA:

Results below are based on the product.

96 hour static acute LC50 to Bluegill Sunfish = 121 ppm



PRODUCT

NALCO 71-D5 ANTIFOAM

Emergency Telephone Number

Medical (800) 462-5378 (24 hours)

(800) 1-M-ALERT

SECTION 12 ENVIRONMENTAL INFORMATION

(CONTINUED)

TOXICITY RATING: Slightly toxic

96 hour static acute LC50 to Rainbow Trout = 113 ppm

TOXICITY RATING: Slightly toxic

48 hour static acute LC50 to Daphnia Magna = 6.5 mg/L

48 hour no observed effect concentration is 0.33 mg/L based on no mortality or abnormal effects.

TOXICITY RATING: Toxic

96 hour static acute LC50 to Fathead minnow = 190 mg/L

96 hour no observed effect concentration is less than 100 mg/L based on no mortality or abnormal effects.

TOXICITY RATING: Slightly toxic

If released into the environment, see CERCLA in Section 14.

SECTION 13 TRANSPORTATION INFORMATION

PROPER SHIPPING NAME/HAZARD CODE -
(DEPENDENT UPON MODE, PACKAGE)

PRODUCT IS NOT REGULATED
DURING TRANSPORTATION

SECTION 14 REGULATORY INFORMATION

The following regulations apply to this product.

FEDERAL REGULATIONS:

OSHA'S HAZARD COMMUNICATION RULE, 29 CFR 1910.1200:

Based on our hazard evaluation, the following ingredients in this product are hazardous and the reasons are shown below.

Kerosene - Skin irritant

Straight run middle distillates - Skin irritant

Straight run middle distillates (oil mist) = TWA 5 mg/m³,
STEL 10 mg/m³ ACGIH/TLV

Kerosene (oil mist) = TWA 5 mg/m³, STEL 10 mg/m³ ACGIH/TLV



PRODUCT

NALCO 71-D5 ANTIFOAM

Emergency Telephone Number

Medical (800) 462-5378 (24 hours)

(800) I-M-ALERT

SECTION 14 REGULATORY INFORMATION

(CONTINUED)

Straight run middle distillates (oil mist) = TWA 5 mg/m³ OSHA/PEL
Kerosene (oil mist) = TWA 5 mg/m³ OSHA/PEL

Kerosene = TWA 100 ppm TLV
Manufacturer's recommendation

CERCLA, 40 CFR 117, 302:
Notification of spills of this product is not required.

SARA/SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986
(TITLE III) - SECTIONS 302, 311, 312 AND 313:

SECTION 302 - EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355):
This product does not contain ingredients listed in Appendix A and B as an Extremely Hazardous Substance.

SECTIONS 311 and 312 - MATERIAL SAFETY DATA SHEET REQUIREMENTS (40 CFR 370):
Our hazard evaluation has found this product to be hazardous. The product should be reported under the following EPA hazard categories:

- XX Immediate (acute) health hazard
- Delayed (chronic) health hazard
- Fire hazard
- Sudden release of pressure hazard
- Reactive hazard

SECTION 313 - LIST OF TOXIC CHEMICALS (40 CFR 372):
This product does not contain ingredients on the List of Toxic Chemicals.

TOXIC SUBSTANCES CONTROL ACT (TSCA):
The chemical ingredients in this product are on the 8(b) Inventory List (40 CFR 710).

FOOD AND DRUG ADMINISTRATIONS (FDA) Federal Food, Drug and Cosmetic Act:
When use situations necessitate compliance with FDA regulations, this product is acceptable under 21 CFR 176.210 defoaming agents used in the manufacture of paper and paperboard.

RESOURCE CONSERVATION AND RECOVERY ACT (RCRA), 40 CFR 261 SUBPART C & D:
Consult Section 11 for RCRA classification.

FEDERAL WATER POLLUTION CONTROL ACT, CLEAN WATER ACT, 40 CFR 401.15
(formerly Sec. 307), 40 CFR 116 (formerly Sec. 311):



MATERIAL SAFETY DATA SHEET

PRODUCT

NALCO 71-D5 ANTIFOAM

Emergency Telephone Number

Medical (800) 462-5378 (24 hours)

(800) I-M-ALERT

(CONTINUED)

SECTION 14 REGULATORY INFORMATION

None of the ingredients are specifically listed.

CLEAN AIR ACT, Sec. 111 (40 CFR 60), Sec. 112 (40 CFR 61, 1990 Amendments),
Sec. 611 (40 CFR 82, CLASS I and II Ozone depleting substances):
This product contains the following ingredients covered by the Clean Air Act:

Polypropylene glycol - Section 111

STATE REGULATIONS:

CALIFORNIA PROPOSITION 65:

This product does not contain any chemicals which require warning under
California Proposition 65.

MICHIGAN CRITICAL MATERIALS:

This product does not contain ingredients listed on the Michigan Critical
Materials Register.

STATE RIGHT TO KNOW LAWS:

The following ingredient(s) are disclosed for compliance with State Right To
Know Laws:

Kerosene
Oxyalkylate
Polyglycol
Polyglycol acid ester
Straight run middle distillate

8008-20-6
Trade secret
Trade secret
Trade secret
64741-44-2

INTERNATIONAL REGULATIONS:

This is a WHMIS controlled product under The House of Commons of Canada Bill
C-70 (Class D2B). The product contains the following substance(s), from the
Ingredient Disclosure List or has been evaluated based on its toxicological
properties, to contain the following hazardous ingredient(s):

Chemical Name	CAS #	% Concentration Range
Kerosene	8008-20-6	10-20
Straight run middle distillates	64741-44-2	40-70

SECTION 15 ADDITIONAL INFORMATION

None

PAGE 7 OF 9



PRODUCT

NALCO 71-D5 ANTIFOAM

Emergency Telephone Number

Medical (800) 462-5378 (24 hours)

(800) I-M-ALERT

SECTION 16 USER'S RESPONSIBILITY

This product material safety data sheet provides health and safety information. The product is to be used in applications consistent with our product literature. Individuals handling this product should be informed of the recommended safety precautions and should have access to this information. For any other uses, exposures should be evaluated so that appropriate handling practices and training programs can be established to ensure safe workplace operations. Please consult your local sales representative for any further information.

SECTION 17 BIBLIOGRAPHY

ANNUAL REPORT ON CARCINOGENS, U.S. Department of Health and Human Services, Public Health Service, PB 33-135855, 1983.

CASARETT AND DOULL'S TOXICOLOGY, THE BASIC SCIENCE OF POISONS, Doull, J., Klaassen, C. D., and Adair, M. O., eds., Macmillan Publishing Company, Inc., N. Y., 2nd edition, 1980.

CHEMICAL HAZARDS OF THE WORKPLACE, Proctor, N. H., and Hughes, J. P., eds., J. P. Lipincott Company, N.Y., 1981.

DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS, Sax, N. Irving, ed., Van Nostrand Reinhold Company, N.Y., 6th edition, 1984.

IARC MONOGRAPHS ON THE EVALUATION OF THE CARCINOGENIC RISK OF CHEMICALS TO MAN, Geneva: World Health Organization, International Agency for Research on Cancer, 1972-1977.

PATY'S INDUSTRIAL HYGIENE AND TOXICOLOGY, Clayton, G. D., Clayton, F. E., eds., John Wiley and Sons, N. Y., 3rd edition, Vol. 2 A-C, 1981.

REGISTRY OF TOXIC EFFECTS ON CHEMICAL SUBSTANCES, U.S. Department of Health and Human Services, Public Health Service, Center for Disease Control, National Institute for Occupational Safety and Health, 1983 supplement of 1981-1982 edition, Vol. 1-3, OH, 1984.

Title 29 Code of Federal Regulations Part 1910, Subpart Z, Toxic and Hazardous Substances, Occupational Safety and Health Administration (OSHA).

THRESHOLD LIMIT VALUES FOR CHEMICAL SUBSTANCES AND PHYSICAL AGENTS IN THE WORKROOM ENVIRONMENT WITH INTENDED CHANGES, American Conference of Governmental Industrial Hygienists, OH.



PRODUCT

NALCO 71-D5 ANTIFOAM

Emergency Telephone Number

Medical (800) 462-5378 (24 hours)

(800) I-M-ALERT

SECTION 17 BIBLIOGRAPHY

(CONTINUED)

PREPARED BY: Ricky A. Stackhouse PhD., Toxicologist

DATE CHANGED: 11/30/93

DATE PRINTED: 06/06/94



PRODUCT

Emergency Telephone Number

Medical (800) 462-5378 (24 hours)

(800) I-M-ALERT



MATERIAL SAFETY DATA SHEET

PRODUCT

GI717 ACIDIC PH ADJUSTOR

Emergency Telephone Number

Medical (800) 462-5378 (24 hours)

(800) I-M-ALERT

SECTION 1 PRODUCT IDENTIFICATION

TRADE NAME: GI717 ACIDIC PH ADJUSTOR
DESCRIPTION: A phosphoric acid solution

NFPA 704M/HMIS RATING: 2/2 HEALTH 0/0 FLAMMABILITY 0/0 REACTIVITY 0 OTHER
0=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme

SECTION 2 HAZARDOUS INGREDIENTS

Our hazard evaluation has identified the following chemical ingredient(s) as hazardous under OSHA's Hazard Communication Rule, 29 CFR 1910.1200. Consult Section 14 for the nature of the hazard(s).

INGREDIENT(S)	CAS #	APPROX.%
Phosphoric acid	7664-38-2	40+

SECTION 3 PRECAUTIONARY LABEL INFORMATION

WARNING: Causes burns to skin and eyes. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield when handling. Avoid prolonged or repeated breathing of vapor. Use with adequate ventilation. Do not take internally.

Empty containers may contain residual product. Do not reuse container unless properly reconditioned.

SECTION 4 FIRST AID INFORMATION

EYES: Immediately flush for at least 15 minutes while holding eyelids open. Call a physician at once.
SKIN: Immediately flush with water for at least 15 minutes. For a large splash, flood body under a shower. Call a physician at once.
INGESTION: Do not induce vomiting. Give water. Call a physician at once.
INHALATION: Remove to fresh air. Treat symptoms. Call a physician.

NOTE TO PHYSICIAN: No specific antidote is known. Based on the individual reactions of the patient, the physician's judgment should be used to control symptoms and clinical condition.

CAUTION: If unconscious, having trouble breathing or in convulsions, do not induce vomiting or give water.

**MATERIAL SAFETY DATA SHEET****PRODUCT**

GI717 ACIDIC PH ADJUSTOR

Emergency Telephone Number

Medical (800) 462-5378 (24 hours)

(800) I-M-ALERT

SECTION 5 HEALTH EFFECTS INFORMATION**PRIMARY ROUTE(S) OF EXPOSURE:** Eye, Skin, Inhalation

EYE CONTACT: Corrosive to the eyes with possible permanent damage depending on the length of exposure and on the first aid action given.

SKIN CONTACT: Corrosive to the skin with possible permanent damage depending on the length of exposure and on the first aid action given.

INGESTION: Severe internal irritation and damage can result.

INHALATION: May cause irritation to the respiratory tract and lungs.

SYMPTOMS OF EXPOSURE: A review of available data does not identify any symptoms from exposure not previously mentioned, or identified in Section 6 or 14.

AGGRAVATION OF EXISTING CONDITIONS: A review of available data does not identify any worsening of existing conditions not previously mentioned, or identified in Section 6 or 14.

SECTION 6 TOXICOLOGY INFORMATION

ACUTE TOXICITY STUDIES: Acute toxicity studies have been conducted on this product. The results are shown below.

ACUTE ORAL TOXICITY (ALBINO RATS): LD50 = 1,530 mg/kg

ACUTE DERMAL TOXICITY (ALBINO RABBITS): LD50 = 2,740 mg/kg

PRIMARY SKIN IRRITATION TEST (ALBINO RABBITS):

SKIN IRRITATION INDEX DRAIZE RATING: Extremely irritating (Corrosive)

PRIMARY EYE IRRITATION TEST (ALBINO RABBITS):

EYE IRRITATION INDEX DRAIZE RATING: Extremely irritating (Corrosive)

SECTION 7 PHYSICAL AND CHEMICAL PROPERTIES

COLOR: Pale yellow

DENSITY:

SPECIFIC GRAVITY:

pH (NEAT) =

VISCOSITY:

BOILING POINT:

FLASH POINT:

FORM: Liquid

13.2 lbs/gal.

1.58 @ 74 Degrees F

Less than 1.0

21 cps @ 74 Degrees F

217 Degrees F @ 760 mm Hg

None (PMCC)

ASTM D-1298

ASTM E-70

ASTM D-2983

ASTM D-86

ASTM D-93



MATERIAL SAFETY DATA SHEET

PRODUCT

GI717 ACIDIC PH ADJUSTOR

Emergency Telephone Number

Medical (800) 462-5378 (24 hours)

(800) I-M-ALERT

SECTION 7 PHYSICAL AND CHEMICAL PROPERTIES

(CONTINUED)

NOTE: These physical properties are typical values for this product.

SECTION 8 FIRE AND EXPLOSION INFORMATION

FLASH POINT: None (FMCC) ASTM D-93

EXTINGUISHING MEDIA: Based on the NFPA guide, use dry chemical, alcohol foam, carbon dioxide or other extinguishing agent suitable for Class B fires. Use water to cool containers exposed to fire. For large fires, use water spray or fog, thoroughly drenching the burning material.

UNUSUAL FIRE AND EXPLOSION HAZARD: May evolve phosphoric oxide fumes under fire conditions.

SECTION 9 REACTIVITY INFORMATION

INCOMPATIBILITY: Avoid alkaline materials (eg. ammonia and its solutions, carbonates, sodium hydroxide (caustic), potassium hydroxide, calcium hydroxide (lime), cyanides, sulfides, hypochlorites, chlorites) which can generate heat with splattering or boiling and the release of toxic fumes.

THERMAL DECOMPOSITION PRODUCTS: In the event of combustion, phosphoric oxide fumes may be formed. Do not breathe smoke or fumes. Wear suitable protective equipment.

SECTION 10 PERSONAL PROTECTION EQUIPMENT

RESPIRATORY PROTECTION: If it is possible to generate significant levels of vapors or mists, a NIOSH approved or equivalent respirator is recommended.

For large spills, entry into large tanks, vessels or enclosed small spaces with inadequate ventilation, a pressure-demand, self-contained breathing apparatus is recommended.

VENTILATION: General ventilation is recommended. Additionally, local exhaust ventilation is recommended where mists or aerosols may be released.

PROTECTIVE EQUIPMENT: Wear gloves, boots, apron and a face shield with chemical splash goggles (ANSI Z 87.1 requirements and selection of gloves, goggles, shoes, etc.). A full slicker suit is recommended if gross exposure is possible.

The availability of an eye wash fountain and safety shower is recommended.



MATERIAL SAFETY DATA SHEET

PRODUCT

GI717 ACIDIC PH ADJUSTOR

Emergency Telephone Number

Medical (800) 462-5378 (24 hours)

(800) I-M-ALERT

SECTION 10 PERSONAL PROTECTION EQUIPMENT

(CONTINUED)

If clothing is contaminated, remove clothing and thoroughly wash the affected area. Launder contaminated clothing before reuse.

SECTION 11 SPILL AND DISPOSAL INFORMATION

IN CASE OF TRANSPORTATION ACCIDENTS, CALL THE FOLLOWING 24-HOUR TELEPHONE NUMBER (800) I-M-ALERT or (800) 462-5378.

SPILL CONTROL AND RECOVERY:

Small liquid spills: Contain with absorbent material, such as clay, soil or any commercially available absorbent. Shovel reclaimed liquid and absorbent into recovery or salvage drums for disposal. Refer to CERCLA in Section 14.

Large liquid spills: Dike to prevent further movement and reclaim into recovery or salvage drums or tank truck for disposal. Refer to CERCLA in Section 14.

DISPOSAL: If this product becomes a waste, it meets the criteria of a hazardous waste as defined under the Resources Conservation and Recovery Act (RCRA) 40 CFR 261. Hazardous Waste D002.

As a hazardous liquid waste, it must be solidified with stabilizing agents (such as sand, fly ash, or cement) so that no free liquid remains before disposal to a licensed industrial waste landfill (Hazardous Waste Treatment, Storage and Disposal facility). A hazardous liquid waste can also be incinerated in accordance with local, state, and federal regulations.

SECTION 12 ENVIRONMENTAL INFORMATION

If released into the environment, see CERCLA in Section 14.

SECTION 13 TRANSPORTATION INFORMATION

PROPER SHIPPING NAME/HAZARD CODE - (DEPENDENT UPON MODE, PACKAGE)	PHOSPHORIC ACID 8, UN 1805, PG III
--	---------------------------------------

SECTION 14 REGULATORY INFORMATION

The following regulations apply to this product.

FEDERAL REGULATIONS:

OSHA HAZARD COMMUNICATION RULE, 29 CFR 1910.1200: